

MN Polish (*Liquid Wax*)

Liquid polish for polished natural stone

Description

A special product from the LITHOFIN-Range for marble, natural and engineered stone (MN). Solvent based polishing liquid containing high quality waxes.

Note: Lithofin MN Liquid Wax does not contain any environmentally problematic, trichlorethen or similar solvents.

Technical data:

Density: approx. 0,80 g/cm³

Appearance: liquid, colourless, clear

Odour: aromatic

pH-Value: n.a.

Flash Point: >23°C

Solubility in Water: not soluble

Properties

High quality raw materials guarantee optimal protective and maintenance properties, easy polishing and high durability. The first application already produces a polishable film, which can be brought to a high gloss through polishing by hand or machine. Lithofin MN Liquid Wax improves the stone's appearance by enhancing the colour structure and facilitates regular maintenance.

Durability: Resistant to regular household dirt and salt, not resistant to petrol and similar substances. Depending on the level of wear and tear, the product's effect will last for several months.

Field of use

For the initial treatment of natural and engineered stone. Improves the appearance and protects the surface. Can also be used to touch up matt and dull spots.

Surfaces: All finely honed and polished natural stones such as marble, limestone, travertine, slate, granite, etc. as well as engineered stone, marble and terrazzo.

Directions for use

Shake bottle before use. Thinly and evenly apply Lithofin Liquid Wax with a clean cloth and allow the product to dry. Then polish with a soft linen cloth or polishing pad. Highly absorbent surfaces may have to be treated more than once.

Please Note: The surface to be treated must be completely clean and dry. Protect surfaces sensitive to solvents. Lithofin MN Liquid Wax is suitable for indoor use only. Well honed surfaces are a prerequisite for good results. In case the application is patchy, polish off with steel wool (000).

Layer forming products affect the slip resistant properties of the surface. We highly recommend testing this product in an inconspicuous area prior to use.

Lithofin MN Polish (liquid-wax) can be removed with Lithofin MN Power-Clean or in extremely stubborn cases with Lithofin WAX-OFF.

On smaller surfaces, use Lithofin MN Polish Cream.

Application temperature: The temperature of the surface should be between 10°C and 30°C. Switch off under floor heating. Avoid direct sunlight.

Drying time: Approx. 60 minutes.

Coverage: Approx. 15 to 20m² per litre depending on the surface.

Storage

Keep closed and dry at room temperature. Do not store in temperatures below 12°C. Shelf life of three years.

Environmental protection

Contains solvents, free of chlorinated hydrocarbons.

Disposal: Liquid product is classified as special waste.

Containers are made of environmentally friendly tin plate. Clean containers can be recycled through collection systems.

Safety

Contents: Naphtha hydrodesulphurized heavy (30% to 60%); xylene (10% to 30%); auxiliary agents.

Risk and safety phrases: Flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep out of the reach of children. Do not breathe vapour. Avoid contact with skin. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

First aid procedures: Remove contaminated clothing immediately. In case of inhalation, seek fresh air. In the event of symptoms refer for medical treatment. In case of contact with skin wash off immediately with soap and water. In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. In case of ingestion, do not induce vomiting. If swallowed drink plenty of water and seek medical treatment.

Emergency procedures: In case of spill or other release, soak up with absorbent material (eg. sand, sawdust, and general-purpose binder). In case of fire formation of dangerous gases possible. Suitable extinguishing material: foam, dry powder, carbon dioxide, sand.

Additional information: Is listed on the Material Safety Data Sheet.

ADR2003:

Flammable liquid, n.o.s.

UN 1993, Class 3

Packaging Group III

Packaging

1 litre bottle with child-proof cap (12 per box)

This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Where no previous experiences is available, or in cases of doubt, test the product in an inconspicuous area. (AU12.03gps/7.03)