

Cleaning - Protecting - Maintaining Quartzite and Sandstone rough, sawn -outdoor- e.g. Dholpur, Mint, Modak, etc.

Sandstone and quartzite are often used outdoors because they are naturally slip resistant. These stones are robust and hard wearing, some types tend to stain quite easily though. The correct treatment -from the beginning- is important for this natural material and guarantees the optimal appearance for many years.

Overview of the 3 Steps *for more detailed instructions, please refer to Page 2*

1

Initial cleaning of newly installed surfaces *used surfaces: Page 2*

Lithofin MN Builders' Clean removes cement residues and leaves a clean and clear surface.




Coverage:
1Ltr./10m²



Dilute product 1:10 with water.




Remove the solution from the surface.



Remove the solution from the surface.



Rinse well with plenty of clear water.



Allow the surface to dry.

Please Note:
Always test the product in an inconspicuous area. Some stones may turn matt or change in colour.

Necessary equipment: bucket, scrubbing brush, squeegee or wet-and-dry vacuum

2a

Protecting against stains *initial cleaning of used surfaces: Page 2*


Lithofin MN Stain-Stop -invisible- protects against oil and water and simplifies maintenance



Coverage:
1Ltr./5m²



Please note.




Pour product in a basin or bucket.




Evenly apply with a roller or brush.



Distribute or remove excess product, streaks and puddles.



Allow to dry. Do not walk on surface for approx. 45 minutes.



Protect from water for 24 hours.

2b



Coverage:
1Ltr./10m²

Enhancing the appearance -alternative to 2a-

Lithofin MN Colour Intensifier renders the stone water repellent and enhances the natural colour - not suitable for very porous sandstones.

initial cleaning of used surfaces: Page 2

Method as described in 2a.

Necessary equipment: bucket or basin, roller or brush, cloth

3

Regular maintenance

Lithofin MN Power-Clean for removing surface dirt as needed.



Dilute product 1:3 with water.



Scrub the floor and rinse with clear water once.

Necessary equipment: bucket, scrubbing brush, mop.

Please follow the detailed instructions on the product label. *for additional information, please refer to Page 2*

Newly installed surfaces

Before grouting: thinly apply Lithofin MN Stain-Stop or Lithofin SPLASH-STOP to the dry surface before grouting. This treatment will simplify removing excess grouting material because the surface will be water repellent.

1 Cleaning and refurbishing used or extremely dirty surfaces

- ◆ Before treating used surfaces, the stone must be thoroughly cleaned. All deposits and care product residues must be removed from the surface and from the pores.
- Apply Lithofin MN Power-Clean.
- Scrub well with either a scrubbing brush or machine.
- Rinse well with clear water until all product residues are gone from the surface.
- ◆ Other, stubborn types of dirt: please refer to the table below.
- ◆ Allow the surface to dry for several days before applying the protective treatment.

Other, stubborn types of dirt

cement residues, builders' dirt, limescale	Lithofin MN Builders' Clean
tar, wax, varnish, paint	Lithofin WAX-OFF
deeply engrained oil stains	Lithofin OIL-EX

2 Weitere Angaben zur Oberflächenbehandlung

- ◆ Protective treatments enhance the appearance and make natural stone less sensitive.
- ◆ The protective effect prevents staining or at least simplifies removing stains.
- ◆ The natural stone surface becomes easier to maintain and stays beautiful for many years.
- ◆ Lithofin MN Colour Intensifier enhances the stone's appearance by invigorating the natural colour structure. An invisible water repellent effect is reached with Lithofin SPLASH-STOP.
- ◆ Lithofin MN Stain-Stop provides optimal protection against water, oil and grease. Alternatively, the nearly odourless Lithofin MN Stain-Stop "W" can be used.
- ◆ Repeat the protective treatment after 4 to 5 years (Lithofin MN Colour Intensifier 1 to 2 years).

Please Note:

- ◆ **Always test the product in an inconspicuous area.** Non-absorbent or wet surfaces cannot be treated.
- ◆ Use impregnators only on completely dry surfaces. Otherwise, the product will not be able to penetrate into the surface.
- ◆ Apply the product evenly. Do not allow streaks or puddles to dry.
- ◆ Carefully remove any excess product off the surface.
- ◆ Some types of stone may turn slightly darker after treatment with Lithofin MN Stain-Stop or Lithofin SPLASH-STOP.
- ◆ In case the stone is laid in sand, treat the back side with Lithofin SPLASH-STOP or Lithofin MN Stain-Stop prior to laying. This will prevent discolouration caused by water pushing from below.

Please Note:

△ Please follow the detailed instructions on the label.

△ Hard stones are mostly resistant to acid. Some types (e.g. Blue Pearl, Bahia blue, Chinese granites, etc.) do, however, react by turning matt or discoloured. Always test in an inconspicuous area before using acidic cleaners. △ When treating gabbros (Impala, Nero Assoluto, etc.) always apply the product thinly and very evenly because

these stones are not very absorbent. Test prior to use.

TIP: Avoid leaching and strong degreasing products as well as products that build up layers. These products alter the appearance and make maintenance more difficult.

△ This information should be considered to be informal and non-binding. The products must be used according to local conditions and materials. Instructions must be read carefully and followed closely. Where no previous experience is available, or in cases of doubt, test the product in an inconspicuous area. (AU7.06gps/5.06)

Agents for Australia:

CDK Stone Pty. Ltd. · Moorabbin 3189 · Phone (Melbourne): (03) 9553 3055 · Phone (Sydney): (02) 9518 0971

Manufactured in Germany by: LITHOFIN AG · 73240 Wendlingen · e-Mail: info@lithofin.de

www.lithofin.com